

# MV cables Tools

## MF3/60



### Certifications

Approved by ENEDIS

### Section

MV Multifunction

### Application

Field  
Laboratory



### PRODUCT BENEFITS

Tuning of the pitch of the tool  
Embedded wear pads to protect the tool from the contact with the outer sheath

### TOOL CAPACITY

Diameter	16 - 58 mm 0,630 - 2,283 inch
Peelable semi conductor thickness capacity	0.4 - 1.5 mm
Insulation thickness capacity	7 mm
Stylus Included	SR

### TOOL DIMENSIONS

Length	305 mm
Width	115 mm
Height	165 mm
Weight without box	1,75 Kg
Packaging	None

### ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE  
Phone: +33 2 43 71 11 80  
Fax number : +33 2 43 71 16 51  
www.alroc.fr

## Multifunction tool for outer sheath, peelable semiconductor and insulation

### TO DO WHAT

The MF3/60 tools enables the user to :  
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut  
Score the peelable semiconductor (with the SR scoring stylus delivered with the tool)  
Set the length to be removed and remove the insulation with a straight and neat cut



### Options

SRC - Scoring stylus for peelable semiconductor with chamfer  
SCH - Chamfering stylus for insulation

### Spare part

KIT-MF3/40 - Protective wear pads  
SR - Scoring stylus for peelable semiconductor  
LS - Spare blade for peelable semiconductor  
LMF2 - Spare blade for primary insulation  
BR - Thrust to set the length of insulation to be remove  
VBB1 - Screw for locking the thrust  
PCR - Quick set up right angled 45° handle  
196855 - Straight handle M10  
108098 - Clamping knob for blade

### Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath  
ROTO-TMG - Connector holder for bolted and clamping connections  
DSP - Peelable semiconductor lifter



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Peelable semi conductor thickness capacity	Insulation thickness capacity	Stylus Included	Length	Width	Height	
MF3/40	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-C	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SR	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SRC	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/40-SSR	16 - 40 mm 0,630 - 1,575 in	Option	7 mm	None	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	none
MF3/60	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-C	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SR	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SRC	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SSR	16 - 58 mm 0,630 - 2,283 in	Option	7 mm	None	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none